

## INFOPRINT 6700 THERMAL PRINTERS

### HIGHLIGHTS

- Prints up to 10 inches per second (ips) (254 mm per second)<sup>1</sup> in 4-, 6- and 8-inch widths at up to 300 dots per inch (dpi) resolution
- Facilitates multi-protocol RFID support on 4-inch model R40<sup>2</sup>
- Offers remote printer management and migration tools to enable effective supply chain management
- Helps improve efficiency by providing one of the largest ribbon capacities and intelligent media detection capabilities
- Provides support for multiple emulations in base engine with auto-switch interpreter via print queues
- Integrates with IBM middleware to facilitate centralised communication.



### KEEP YOUR INFORMATION FLOWING

In high-volume industrial environments, reliable output management and RFID capability are critical to supply chain efficiency. To keep your information flowing, InfoPrint Solutions Company offers easy-to-use InfoPrint 6700 thermal printers that provide flexible media handling, support for barcodes (optional integrated barcode validator) and RFID tags including EPCglobal Class 1 Gen2 and powerful remote management capabilities. Three models – R40, R60 and R80 – provide choices in media width and speed. The InfoPrint 6700 family also includes a model designed specifically for mid-volume operations.

By integrating InfoPrint 6700 printers with IBM's middleware architecture, you can monitor printer activities and output processes. With additional support for RFID tags,<sup>2</sup> as well as an upgrade path to the next generation of RFID technology, InfoPrint Solutions Company can provide you with an end-to-end output management solution.

### REDUCE DOWNTIME WITH SUPERIOR PRINTER RELIABILITY

Exceptional print quality and performance are inherent to the thermal printhead control technology of InfoPrint 6700 printers. With an exclusive snap-in printhead feature, operators can quickly change printheads and switch from 203 dpi to 300 dpi. An improved power

processor provides fast emulation to support an easy transition from your existing industrial printers. Two direct drive motors control the ribbon spindles and are designed to sustain ribbon tension throughout the life of the printer, to help reduce instances of torn ribbons and clutch replacement – and resulting downtime.

#### **CREATE A USER-FRIENDLY PRINT ENVIRONMENT WITH INTUITIVE PRINTER FEATURES**

InfoPrint 6700 thermal printers simplify form loading and supply replacement with easy access to internal components. The user-friendly front panel controls and backlit displays facilitate straightforward printer setup and storage of customised printer configurations. An optional cutter and tray provide additional flexibility by enabling operators to cut and collect labels as they are printed.

Use the InfoPrint Solutions Company Printer Management Utility on InfoPrint 6700 printers and you can more easily manage and configure multiple printers with an intuitive interface that enables proactive alert notification. And by leveraging proven software migration tools, you can begin the transition from barcodes to RFID technology.

#### **MINIMISE ERRORS WITH BARCODE AND RFID VALIDATION**

InfoPrint 6700 thermal printers offer optional integrated barcode and RFID validation. To help ensure high print quality and minimise errors and costly reprints, InfoPrint 6700 printers can detect, mark out and reprint unreadable barcodes and defective labels without user intervention.

#### **OPTIMISE YOUR SUPPLY CHAIN OUTPUT WITH THE INFOPRINT 6700 FAMILY**

The InfoPrint 6700 family includes printers designed for high-volume and mid-volume operations. Ask your InfoPrint Solutions

Company representative to help assess your needs and recommend the model that meets your functional requirements and total cost of ownership (TCO) objectives.

#### **RELY ON TIME-TESTED INFOPRINT SOLUTIONS COMPANY OUTPUT SERVICES, SUPPLIES AND EXPERIENCE**

InfoPrint Solutions Company professionals are available around-the-clock to provide you with a full range of services. To learn more about the reliable line of InfoPrint 6700 thermal printers, contact your InfoPrint Solutions Company representative or visit:

**[infoprint.com](http://infoprint.com)**

InfoPrint 6700 thermal label printer supplies are designed to enhance your printing capabilities and to help prevent premature printhead wear. For a complete list of supplies, visit:

**[infoprint.com/supplies](http://infoprint.com/supplies)**

## INFOPRINT 6700 THERMAL PRINTER

Item	Specifications
<b>Print Speed<sup>1</sup> and resolution</b>	<b>Models R40/R60:</b> up to 10 ips @ 203 dpi (254 mm/sec) 8 ips @ 300 dpi (203 mm/sec) <b>Model R80:</b> up to 8 ips @ 203 dpi (203 mm/sec) 6 ips @ 300 dpi (152 mm/sec)
<b>Memory (std/max)</b>	Flash: 8 MB/16 MB maximum DRAM: 32 MB maximum
<b>Printing methods</b>	Thermal transfer or direct thermal, selectable from the operator panel.
<b>Printable width</b>	<b>Model R40:</b> 4.5" (114 mm) maximum <b>Model R60:</b> 6.8" (172 mm) maximum <b>Model R80:</b> 8.75" (222 mm) maximum
<b>Media handling</b>	Tear-off mode; peel-off mode; tear-off strip mode; batch (rewind) mode Optional cutter and tray for unattended operation
<b>Media compatibility</b>	
Media types	Roll or fanfold; labels, tags and tickets; paper, film or synthetic stock; thermal transfer or direct thermal
Media width	<b>Model R40:</b> .75" to 4.5" (19 mm to 114 mm); ribbon width: 1" to 4.5" (25.4 mm to 114 mm) <b>Model R60:</b> 2" to 6.8" (51 mm to 171 mm) <b>Model R80:</b> 3" to 8.75" (76 mm to 222 mm)
Media thickness	.0025" to .0010" (.07 mm to .25 mm)
Roll core diameter	3" (76 mm)
Maximum roll diameter	8" (209 mm)
Thermal transfer ribbons	Standard ribbon length: 2,050 feet (625 m)
<b>Datastream/programming language support</b>	ASCII (LP+); IGP (PGL); Code V (VGL); IGL; STGL; TGL; ZGL; InfoPrint Solutions Company Intelligent Printer Data Stream (IPDS) (optional); TN5250/3270 (optional)
<b>Barcodes</b>	Code 39; Code 128 (A,C), Codabar, Interleaved 2 of 5; FIM UPC-A; UPC-E; UPC-EO; EAN 8; EAN 13; Code 93; Postnet; Postbar UCC/EAN 128; PDF 417; UPS Maxicode; Royal Mail, Datamatrix <sup>3</sup>
<b>RFID<sup>2</sup></b>	EPCglobal Class 1 Gen2 For a full list of supported tags, please visit: <a href="http://www.infoprint.com/thermal">www.infoprint.com/thermal</a>
<b>Interface drivers</b>	
Standard interfaces	RS-232/USB 2.0/IEEE 1284 (Centronics)
Optional interfaces	Coax/Twinax; Ethernet 10/100 BaseT; Wireless Ethernet
Microsoft® Windows® drivers	Windows XP; Windows 2000 and Windows NT®
<b>Power requirements</b>	
Consumption	Maximum typical: 115/240 VAC 80/160 185 Watts PowerFactor Correction
Regulatory compliance	FCC-D; UL; CSA; CE
<b>Physical characteristics</b>	<b>Model R40:</b> 11.7" x 20.5" x 13" (29.7 cm x 52 cm x 33 cm) (WxDxH); 37 lbs/16.7 kg (Weight) <b>Model R60:</b> 13.4" x 20.5" x 13" (34 cm x 52 cm x 33 cm) (WxDxH); 41 lbs/18.5 kg (Weight) <b>Model R80:</b> 15.4" x 20.5" x 13" (39 cm x 52 cm x 33 cm) (WxDxH); 43 lbs/19.5 kg (Weight)

**FOR MORE INFORMATION**

Contact your InfoPrint Solutions Company representative or InfoPrint Solutions Partner or visit:

**infoprint.com**/thermal

**InfoPrint Solutions Company**

PO Box 41  
North Harbour  
Portsmouth  
Hampshire PO6 3AU  
Basingstoke  
United Kingdom

The InfoPrint Solutions Company home page can be found **infoprint.com**

InfoPrint Solutions Company is a trade name of InfoPrint Solutions Company, LLC, in the United States, other countries or both. InfoPrint Solutions Company, LLC is a joint venture of Ricoh Co., Ltd. and International Business Machines Corporation.

InfoPrint and IPDS are trademarks of InfoPrint Solutions Company in the United States, other countries, or both.

IBM is a trademarks of International Business Machines Corporation in the United States, other countries, or both.

Microsoft, Windows and NT are trademarks or registered trademarks of Microsoft Corporation in the United States, other countries or both.

Other company, product and service names may be trademarks, or service marks of others.

<sup>1</sup>Exact speed varies depending on document complexity, system configuration, software application, driver and printer state.

<sup>2</sup>RFID available on R40 model only. Optional feature – 4900 (U.S. and Canada); 4920 (Singapore); 4921 (Australia); 4950 (EMEA select countries only) – required to enable.

<sup>3</sup>See **infoprint.com**/thermal for the complete list of supported barcodes.

References in this publication to InfoPrint Solutions Company products, programs or services do not imply that InfoPrint Solutions Company intends to make these available in all countries in which InfoPrint Solutions Company operates. InfoPrint Solutions Company hardware products are manufactured from new parts, or new and used parts. In some cases, the hardware product may not be new and may have been previously installed. Regardless, InfoPrint Solutions Company warranty terms apply.

© Copyright InfoPrint Solutions Company 2007  
All Rights Reserved.