



More colour. More options. More productivity.



print



copy



scan



fax



finishing
optional



colour

Lexmark **Colour Laser MFPs**

High quality colour meets high power multifunction!



- High performance colour laser multifunction in A4 and A3
- Up to 45 ppm mono, 40 ppm colour printing
- State of the art security features
- Wide range of input and finishing options

X782e

X940e

X945e

LEXMARK
TM

Lexmark **Colour Laser MFPs**

Expand your horizons.



The ultimate multifunction solution

In today's competitive business world, it's more important than ever to ensure your workgroups are armed with all the tools they need to stay productive. One of the most effective ways to achieve this is by integrating Lexmark's highperformance colour MFPs, which consolidate all your critical document functions into a single space saving device. In addition to brilliant colour output and ultra fast print speeds, you'll benefit from advanced scanning, copying, faxing and much, much more!

Attractive yet affordable colour

Lexmark has mastered the art of colour, as well as the art of controlling it! With our newly enhanced toner, you can liven up your business documents with crisp text, rich flesh tones and consistent images from first page to last. And you can also control colour output costs effectively at every level of your workflow. These devices come equipped with a complete range of colour cost control tools, such as colour print permissions and a coverage estimator to assess the cost of a job before printing.

Lexmark **Colour Laser MFPs**

A big touch of simplicity

Now, performing workflow tasks is extraordinarily simple for any type of user. That's because Lexmark's colour-laser MFPs are designed with a super-intuitive, award-winning touch-screen interface. Incredibly large, vivid and fully customisable, it makes working a breeze.

Whether you want to scan documents, print in duplex, pull up email addresses or preview documents as you scan, it's all as easy as a couple of touches of the screen. A world of possibilities at your fingertips!



Total security for true peace of mind

Corporate information is one of your most valuable assets, and protecting it is absolutely critical. Lexmark's colour MFPs come equipped with the most sought after security features to ensure this information always stays safe and sound.

In addition to advanced user access restriction tools, you'll benefit from a wide range of datasecurity features too, from disk wiping and encryption to secure data transmission and confidential printing.



Lexmark **Colour Laser MFPs**

Save time, money and paper

If you're still printing, shipping and processing piles of hardcopies, this may be eating into your profits on a daily basis. Lexmark's colour laser MFPs provide the ideal platform to benefit from Lexmark's enterprise workflow solutions, which include distributed capture, electronic document distribution, on-demand forms and many others. Whether embedded or server based, these solutions help you print less, lower costs, reduce waste and streamline your business processes dramatically.

Ready for anything!

With such a versatile range of options, your possibilities are practically endless! Thanks to the multiple input drawers, you can run diverse paper types or heavy print runs. Then polish off your documents with professional finishing, including stapling (alternative configuration required for X782e). Want to create a banner with your logo, or a special promo on outdoor media? The X782e makes it easy. Want to produce your own catalogues in-house? The A3 models offer a Booklet Finisher, which lets you create dazzling colour booklets in-house.

Which model is perfect for your needs?



Lexmark X782e

- A4 colour MFP for high volume needs
- Printing up to 38 ppm mono, 33 ppm colour
- ColorCare cost control tools
- State of the art security features



Lexmark X940e

- Wide format printing up to A3
- Advanced copy and scan functions
- Printing up to 40 ppm mono, 30 ppm colour
- 1,140-sheet standard input capacity



Fully configured

Lexmark X945e

- Wide format printing up to A3
- Adapted to higher volume output needs
- Printing up to 45 ppm mono, 40 ppm colour
- 3,140-sheet standard input capacity

Lexmark's guarantee to you : At Lexmark, we're always working hard to ensure you achieve maximum productivity and minimum downtime. Our colour-laser MFPs include our solid service guarantee of One Year On Site Repair, with a response time of next business day (in serviceable areas). For an even greater level of peace of mind, you can opt for one of our extended guarantee service offerings. For more information on any of these offerings, just contact your local dealer or visit us today at www.lexmark.co.uk.

Lexmark X782e

Outstanding colour and intuitive interface – a brilliant combination

The Lexmark X782e offers brilliant colour output and a rich range of multifunction features – all in a single high performance, space saving A4 device. And it will boost your productivity with rapid print speeds up to 38 ppm in mono, 33 ppm in colour.

Print Technology

Colour Laser

Function

Colour Copying, Colour Printing, Colour Scanning, Faxing, Colour Network Scanning

Print Speed (A4 mono)

Up to 38 ppm

Print Speed (Letter, Colour)

Up to 35 ppm

Print Speed (A4 colour)

Up to 33 ppm

Print Speed (A4 mono) Duplex

Up to 38 ppm

Print Speed (Letter mono)

Up to 40 ppm

Print Speed (Letter mono) Duplex

Up to 40 ppm

Time to First Page (Black)

as fast as 11 seconds

Time to First Page (Colour)

as fast as 13 seconds

Copy Speed (A4, Black)

Up to 38 cpm

Time to First Copy (Black)

as fast as < 14 seconds

Print Resolution, Black

1200 x 1200 dpi

4800 Color Quality (2400 x 600 dpi)

Print Resolution, Colour

1200 x 1200 dpi, 4800 Color Quality (2400 x 600 dpi)

Scanning Resolution

300 X 300 dpi (colour), 600 X 600 dpi (mono)

Processor

800 MHz

Memory, standard

768 MB

Memory network model, maximum

768 MB

Expandable Memory Options

No

Apple Macintosh Operating Systems Supported

Mac OS X, Mac OS 9.x

Citrix MetaFrame

Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries., Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows Server 2003 running Terminal Server with Citrix MetaFrame XP Presentation Server or

Citrix MetaFrame Presentation Server

3.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 running Terminal Server with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 x64 Edition (Standard, Enterprise) running Terminal Server with Citrix Presentation Server 4.0

Linux Operating Systems Supported

Red Flag Linux Desktop 4.0, 5.0, Linpus Linux Desktop 9.2, 9.3, Red Hat Enterprise Linux WS 3.0, 4.0, 5.0, SUSE Linux Enterprise Server 8.0, 9.0, 10.0, Debian GNU/Linux 3.1, Linspire Linux 5.0, SUSE Linux 10.0, 10.1, 10.2

Microsoft Windows Operating Systems Supported

2000, NT (4.00/4.00 Server), XP, Server 2003, XP x64, Server 2003 running Terminal Server, 2000 Server running Terminal Services, Server 2003 x64 Edition, Server 2003 x64 Edition running Terminal Services, Vista, Vista x64

Novell Operating Systems Supported

Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS), NetWare® 3.2, 4.2 (bindery), NetWare 4.2, 5.x and 6.x (NDS), NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)

UNIX Operating Systems Supported

Sun Solaris SPARC 7, 8, 9, 10, HP-UX 11.00, 11.1, IBM AIX 5.1, 5.2, 5.3, Sun Solaris x86 10

Other Operating Systems Supported

IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform, Virtually any platform supporting TCP/IP

Paper Handling (Standard)

250-Sheet Output Bin, 500-Sheet Drawer, 500-Sheet Tray, Duplex Unit, Second 500-Sheet Drawer, 100-Sheet Multipurpose Feeder

Paper Handling Optional

Banner Media Tray

Paper Input Capacity (Standard)

1600 pages at 80 gsm bond

Paper Input Capacity (Maximum)

1600 pages at 80 gsm bond

Paper Output Capacity (Standard)

250 pages at 80 gsm bond

Paper Output Capacity (Maximum)

250 pages at 80 gsm bond

Copy/Fax/Scan (ADF) Paper Input Capacity

Up to 50 pages at 80 gsm bond

Envelope Capacity

10

Finishing Option

No

Number of Paper Inputs

4

Number of Paper Inputs, Maximum

4

Media Types Supported

Card Stock, Envelopes, Glossy paper, Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide, Banner Paper

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Banner

Standard Ports

Fast Ethernet, USB Compatible with USB 2.0 Specification, USB Direct interface on Operator Panel

Optional Network Ports

Lexmark N4050e 802.11g Wireless Print Server (Print Only), External MarkNet™ N7020e Gigabit Ethernet

Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Socket (Raw TCP/IP), IPP (Internet Printing Protocol), HTTP, NDS Queue-based Printing, NDPS/NEPS (Novell Distributed Print Services, Novell Netware Enterprise Print Services), Enhanced IP (Port 9400)

Network Protocol Support

TCP/IP IPv4, IPX/SPX, AppleTalk™, LexLink (DLC), TCP/IP IPv6

Network Security

SSL Enabled Embedded Web Server, SNMPv3, TCP/IP port access control, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPSec

Printable Area

4.2 mm of the top, bottom, right and left edges (within)

Printer Languages (Standard)

PCL 5c Emulation, PCL 6 Emulation, PPDS, PostScript 3 Emulation, PDF 1.5 Emulation, xHTML, Direct Image

Reduce / Enlarge Range

25 - 400 %

Scan Area, Maximum

216 x 355.6 mm

Modem Speed

33.6 Kbps

Packaged Size (mm - H x W x D)

810 x 795 x 650: 1245 x 1219 x 1016 mm

Size (mm - H x W x D)

1410 x 679 x 584 mm

Weight (kg)

97.5 kg

Noise Level, Idle

31 dBA

Noise Level, Operating

50 dBA

Copier Noise Level, Operating

49 dBA

Scanner Noise Level, Operating

49 dBA

Product Guarantee

One Year Onsite Repair

Product Certifications

CSA, ICES Class A, BSMI Class A, VCCI Class A, FCC Class A, UL 60950-1, IEC 60320-1, CE Class A, CB IEC 60950-1, IEC 60825-1, GS (TUV), SEMKO, UL AR, CS, TÜV Rh, C-tick mark Class A, CCC Class A

Duty Cycle

Up to 150,000 one-time maximum pages per month

Specified Operating Environment

Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3048 Meters (10,000 Feet)

Supplies Yield

6,000*-page (CMYK) Print Cartridges, 10,000*-page (CMYK) High Yield Print Cartridges, 15,000*-page (CMYK) Extra High Yield Print Cartridges. Ships with 10,000*-page black and colour High Yield Return Program Print Cartridges, Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit www.lexmark.com/recycle



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

LEXMARK

Lexmark X940e

Competitive colour MFP for all your wide format needs

Network ready, competitive and easy to use, the Lexmark X940e is the ideal solution for mid-sized workgroups with regular A3 colour needs. Benefit from brilliant colour output and zip through print runs as fast as 40 ppm in mono, 30 ppm in colour.

Print Technology

Colour Laser

Function

Colour Copying, Colour Printing, Faxing, Colour Network Scanning

Print Speed (A4 mono)

Up to 40 ppm

Print Speed (Letter, Colour)

Up to 30 ppm

Print Speed (A4 colour)

Up to 30 ppm

Print Speed (A4 mono) Duplex

Up to 37 spm

Print Speed (Letter mono)

Up to 40 ppm

Print Speed (Letter mono) Duplex

Up to 37 spm

Time to First Page (Black)

as fast as 5 seconds

Time to First Page (Colour)

as fast as 10 seconds

Copy Speed (A4, Black)

Up to 40 cpm

Time to First Copy (Black)

as fast as 6.6 seconds

Print Resolution, Black

2400 Image Quality

Print Resolution, Colour

2400 Image Quality

Scanning Resolution

600 X 300 dpi (colour), 600 X 600 dpi (mono)

Memory, standard

512 MB

Memory network model, maximum

1,024 MB

Expandable Memory Options

Yes

Apple Macintosh Operating Systems Supported

Mac OS X, Mac OS 9.x, Mac OS X (10.4 Intel), Mac OS X (10.4 Power PC)

Citrix MetaFrame

Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries., Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows Server 2003 running Terminal Server with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft

Windows Server 2003 running Terminal Server with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 x64 Edition (Standard, Enterprise) running Terminal Server with Citrix Presentation Server 4.0

Linux Operating Systems Supported

Red Flag Linux Desktop 4.0, 5.0, Linpus Linux Desktop 9.2, 9.3, Red Hat Enterprise Linux WS 3.0, 4.0, 5.0, SUSE Linux Enterprise Server 8.0, 9.0, 10.0, SUSE Linux Professional 9.1, 9.2, 9.3, Debian GNU/Linux 3.1, Linspire Linux 5.0, SUSE Linux 10.0, 10.1, 10.2

Microsoft Windows Operating Systems Supported

2000, NT (4.00/4.00 Server), XP, Server 2003, XP x64, Server 2003 running Terminal Server, 2000 Server running Terminal Services, Server 2003 x64 Edition, Server 2003 x64 Edition running Terminal Services, Vista, Vista x64

Novell Operating Systems Supported

Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS), NetWare® 3.2, 4.2 (bindery), NetWare 4.2, 5.x and 6.x (NDS), NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)

UNIX Operating Systems Supported

Sun Solaris SPARC 7, 8, 9, 10, HP-UX 11.00, 11.1, IBM AIX 5.1, 5.2, 5.3, Sun Solaris x86 10

Other Operating Systems Supported

IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform, Virtually any platform supporting TCP/IP

Paper Handling (Standard)

Integrated Duplex, 100-Sheet Multipurpose Feeder, 520-Sheet Input Tray, 520-Sheet Drawer Stand with Cabinet

Paper Handling Optional

3,500-Sheet Finisher

Paper Input Capacity (Standard)

1140 pages at 80 gsm bond

Paper Input Capacity (Maximum)

1140 pages at 80 gsm bond

Paper Output Capacity (Standard)

400 pages at 80 gsm bond

Paper Output Capacity (Maximum)

3500 pages at 80 gsm bond

Copy/Fax/Scan (ADF) Paper Input

Capacity

Up to 75 pages at 80 gsm bond

Finishing Option

Yes

Number of Paper Inputs

3

Number of Paper Inputs, Maximum

3

Media Types Supported

Card Stock, Envelopes, Glossy paper, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide

Media Sizes Supported

10 Envelope, A3, A4, A5, C5 Envelope, DL Envelope, Executive, Folio, JIS-B4, JIS-B5, Ledger, Legal, Letter, Statement, Universal

Standard Ports

One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified, USB Direct interface on Operator Panel, Gigabit Ethernet (10/100/1000), USB port (Type A) compatible with USB 2.0 Specification

Optional Network Ports

Lexmark N4050e 802.11g Wireless Print Server (Print Only), Internal MarkNet™ N8050 802.11g Wireless, Internal MarkNet™ N8030 Fiber Fast Ethernet

Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Socket (Raw TCP/IP), IPP (Internet Printing Protocol), HTTP, NDS Queue-based Printing, NDPS/NEPS (Novell Distributed Print Services, Novell Netware Enterprise Print Services), Enhanced IP (Port 9400), FTP, TFTP, IPP 1.1 (Internet Printing Protocol)

Network Protocol Support

TCP/IP IPv4, IPX/SPX, AppleTalk™, LexLink (DLC), TCP/IP IPv6

Network Security

SSL Enabled Embedded Web Server, SNMPv3, TCP/IP port access control, Authenticated and encrypted MarkVision Professional communication, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPsec

Printable Area

4.0 mm of the top, bottom, right and left edges (within)

Printer Languages (Standard)

PCL 5c Emulation, PCL 6 Emulation,

PPDS, PostScript 3 Emulation, xHTML, PDF 1.6, Direct Image

Reduce / Enlarge Range

25 - 400 %

Scan Area, Maximum

297 x 432 mm

Modem Speed

33.6 Kbps

Packaged Size (mm - H x W x D)

1480 x 740 x 925 mm

Size (mm - H x W x D)

1153 x 660 x 810 mm

Weight (kg)

173.7 kg

Noise Level, Idle

34 dBA

Noise Level, Operating

52 dBA

Copier Noise Level, Operating

53 dBA

Scanner Noise Level, Operating

54 dBA

Product Guarantee

One Year Onsite Repair

Product Certifications

Energy Star, CSA, ICES Class A, BSMI Class A, VCCI Class A, FCC Class A, UL 60950-1, IEC 60320, CE Class A, CB IEC 60950-1, IEC 60825-1, CISPR 22 Class A, GS (TÜV), SEMKO, UL AR, CS, TÜV Rh, A-tick mark Class A, CCC Class A

Duty Cycle

Up to 150,000 one-time maximum pages per month

Specified Operating Environment

Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2500 Meters (8,200 Feet)

Supplies Yield

Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798., Ships with 13,000*-page black and 12,000*-page colour Toner Cartridges, 22,000*-page colour (CMY) Toner Cartridges, 36,000*-page Black Toner Cartridge



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit www.lexmark.com/recycle



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

LEXMARK

Lexmark X945e

Wide format colour MFP ideal for high volume printing

The ultimate high power workhorse, the Lexmark X945e gives you the quality, speed and versatility you need to keep all your production runs in-house. That includes print speeds up to 45 ppm in mono, 40 ppm in colour, and standard input capacity up to 3,140 sheets.

Print Technology

Colour Laser

Function

Colour Copying, Colour Printing, Faxing, Colour Network Scanning

Print Speed (A4 mono)

Up to 45 ppm

Print Speed (Letter, Colour)

Up to 40 ppm

Print Speed (A4 colour)

Up to 40 ppm

Print Speed (A4 mono) Duplex

Up to 37 spm

Print Speed (Letter mono)

Up to 45 ppm

Print Speed (Letter mono) Duplex

Up to 37 spm

Time to First Page (Black)

as fast as 5.2 seconds

Time to First Page (Colour)

as fast as 10 seconds

Copy Speed (A4, Black)

Up to 45 cpm

Time to First Copy (Black)

as fast as 6.7 seconds

Print Resolution, Black

2400 Image Quality

Print Resolution, Colour

2400 Image Quality

Scanning Resolution

600 X 300 dpi (colour), 600 X 600 dpi (mono)

Memory, standard

512 MB

Memory network model, maximum

1,024 MB

Expandable Memory Options

Yes

Apple Macintosh Operating Systems Supported

Mac OS X, Mac OS 9.x, Mac OS X (10.4 Intel), Mac OS X (10.4 Power PC)

Citrix MetaFrame

Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries., Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows Server 2003 running Terminal Server with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft

Windows Server 2003 running Terminal Server with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 x64 Edition (Standard, Enterprise) running Terminal Server with Citrix Presentation Server 4.0

Linux Operating Systems Supported

Red Flag Linux Desktop 4.0, 5.0, Linpus Linux Desktop 9.2, 9.3, Red Hat Enterprise Linux WS 3.0, 4.0, 5.0, SUSE Linux Enterprise Server 8.0, 9.0, 10.0, SUSE Linux Professional 9.1, 9.2, 9.3, Debian GNU/Linux 3.1, Linspire Linux 5.0, SUSE Linux 10.0, 10.1, 10.2

Microsoft Windows Operating Systems Supported

2000, NT (4.00/4.00 Server), XP, Server 2003, XP x64, Server 2003 running Terminal Services, Server 2003 x64 Edition, Server 2003 x64 Edition running Terminal Services, Vista, Vista x64

Novell Operating Systems Supported

Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS), NetWare® 3.2, 4.2 (bindery), NetWare 4.2, 5.x and 6.x (NDS), NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)

UNIX Operating Systems Supported

Sun Solaris SPARC 7, 8, 9, 10, HP-UX 11.00, 11.1, IBM AIX 5.1, 5.2, 5.3, Sun Solaris x86 10

Other Operating Systems Supported

IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform, Virtually any platform supporting TCP/IP

Paper Handling (Standard)

Integrated Duplex, 100-Sheet Multipurpose Feeder, 520-Sheet Input Tray, 2520-Sheet High Capacity Feeder Stand

Paper Handling Optional

3,500-Sheet Finisher, Booklet Finisher

Paper Input Capacity (Standard)

3140 pages at 80 gsm bond

Paper Input Capacity (Maximum)

3140 pages at 80 gsm bond

Paper Output Capacity (Standard)

400 pages at 80 gsm bond

Paper Output Capacity (Maximum)

3500 pages at 80 gsm bond

Copy/Fax/Scan (ADF) Paper Input

Capacity

Up to 75 pages at 80 gsm bond

Envelope Capacity

not define

Finishing Option

Yes

Number of Paper Inputs

5

Number of Paper Inputs, Maximum

5

Media Types Supported

Card Stock, Envelopes, Glossy paper, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide

Media Sizes Supported

10 Envelope, A3, A4, A5, C5 Envelope, DL Envelope, Executive, Folio, JIS-B4, JIS-B5, Ledger, Legal, Letter, Statement, Universal

Standard Ports

One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified, USB Direct interface on Operator Panel, Gigabit Ethernet (10/100/1000), USB port (Type A) compatible with USB 2.0 Specification

Optional Network Ports

Lexmark N4050e 802.11g Wireless Print Server (Print Only), Internal MarkNet™ N8050 802.11g Wireless, Internal MarkNet™ N8030 Fiber Fast Ethernet

Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Socket (Raw TCP/IP), IPP (Internet Printing Protocol), HTTP, NDS Queue-based Printing, NDPS/NEPS (Novell Distributed Print Services, Novell Netware Enterprise Print Services), Enhanced IP (Port 9400), FTP, TFTP, IPP 1.1 (Internet Printing Protocol)

Network Protocol Support

TCP/IP IPv4, IPX/SPX, AppleTalk™, LexLink (DLC), TCP/IP IPv6

Network Security

SSL Enabled Embedded Web Server, SNMPv3, TCP/IP port access control, Authenticated and encrypted MarkVision Professional communication, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPsec

Printable Area

4.0 mm of the top, bottom, right and left edges (within)

Printer Languages (Standard)

PCL 5c Emulation, PCL 6 Emulation, PPDS, PostScript 3 Emulation, xHTML, PDF 1.6, Direct Image

Reduce / Enlarge Range

25 - 400 %

Scan Area, Maximum

297 x 432 mm

Modem Speed

33.6 Kbps

Packaged Size (mm - H x W x D)

1480 x 740 x 925 mm

Size (mm - H x W x D)

1153 x 660 x 810 mm

Weight (kg)

173.7 kg

Noise Level, Idle

34 dBA

Noise Level, Operating

52 dBA

Copier Noise Level, Operating

53 dBA

Scanner Noise Level, Operating

54 dBA

Product Guarantee

One Year Onsite Repair

Product Certifications

Energy Star, CSA, ICES Class A, BSMI Class A, VCCI Class A, FCC Class A, UL 60950-1, IEC 60320, CE Class A, CB IEC 60950-1, IEC 60825-1, CISPR 22 Class A, GS (TÜV), SEMKO, UL AR, CS, TÜV Rh, A-tick mark Class A, CCC Class A

Duty Cycle

Up to 200,000 one-time maximum pages per month

Specified Operating Environment

Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2500 Meters (8,200 Feet)

Supplies Yield

Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798., Ships with 13,000*-page black and 12,000*-page colour (CMY) Toner Cartridges, 36,000*-page Black Toner Cartridge



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit www.lexmark.com/recycle



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

LEXMARK

